

**!!!IMPORTANT!**

FOR FASTER INSTALL, USE  
DOUBLE-SIDED PVC GRAPHIC  
ADHERED TO THE GLASS WITH  
DOUBLE-SIDED BANNER TAPE  
RATHER THAN WINDOW  
CLINGS.

**GRAPHIC / GLASS PANEL**

**DIMENSIONS:**

28<sup>3/8</sup>"W x 38"H

SAN ANTONIO  
CONVENTION CENTER  
SECTION L2A



**LABOR:**

MEN= 1  
TIME= 1HR

**MATERIAL:**

TRU-CLING  
CLEAR CLING

**TOOLS:**

SQUEEGEE  
DISH SOAP  
SPRAY BOTTLE  
WATER  
PAPER TOWELS  
WINDEX

**DIRECTIONS:**

MIX COLD WATER AND EIGHT  
DROPS OF DISH SOAP IN A  
SPRAY BOTTLE AND SHAKE  
SOLUTION WELL. IF NEEDED,  
CLEAN SURFACE OF GLASS  
WITH WINDEX AND TOWEL  
FIRST. NEXT, SPRAY GLASS  
AND GRAPHIC WITH A LIBERAL  
AMOUNT OF SOLUTION  
BEFORE APPLYING GRAPHIC  
TO THE GLASS. LINE UP AND  
LEVEL OUT GRAPHIC ON  
GLASS. USE SQUEEGEE TO  
REMOVE SOLUTION FROM  
INBETWEEN GRAPHIC AND  
GLASS. WIPE THE GRAPHIC  
CLEAN OF SOLUTION RESIDUE  
BEFORE MOVING TO NEXT JOB.

L2-WC226

FREEMAN PLANTOUR