

DIRECTIONS:

MIX COLD WATER AND EIGHT DROPS OF DISH SOAP IN A SPRAY BOTTLE AND SHAKE SOLUTION WELL. IF NEEDED, CLEAN SURFACE OF GLASS WITH WINDEX AND TOWEL FIRST. NEXT, SPRAY GLASS AND GRAPHIC WITH A LIBERAL AMOUNT OF SOLUTION BEFORE APPLYING GRAPHIC TO THE GLASS. LINE UP AND LEVEL OUT GRAPHIC ON GLASS. USE SQUEEGEE TO REMOVE SOLUTION FROM INBETWEEN GRAPHIC AND GLASS. WIPE THE GRAPHIC CLEAN OF SOLUTION RESIDUE BEFORE MOVING TO NEXT JOB.

SAN ANTONIO
CONVENTION CENTER
SECTION L2A

!!IMPORTANT!

FOR FASTER INSTALL, USE DOUBLE-SIDED PVC GRAPHIC ADHERED TO THE GLASS WITH DOUBLE-SIDED BANNER TAPE RATHER THAN WINDOW CLINGS.

GRAPHIC DIMENSIONS:

A,B= 72^{3/4}"W x 38"H
C= 18"W x 38"H

GLASS PANEL DIMENSIONS:

A,B= 36"W x 38"H
C= 18"W x 38"H

TOOLS:

SQUEEGEE
DISH SOAP
SPRAY BOTTLE
WATER
PAPER TOWELS
WINDEX

LABOR:

MEN= 1
TIME= 1HR

MATERIAL:

TRU-CLING
CLEAR CLING



L2-WC216A

FREEMAN PLANTOUR