
BLDG. LEGEND:

COLUMN DIMENSIONS



LARGE COLUMNS - HALLS A & B ONLY
8'-8" x 9'-6", WITH 10" GAP FOR AIRWALL



MEDIUM COLUMNS - HALL C ONLY
5' DIAMETER / 16' CIRCUMFERENCE



SMALL COLUMNS - HALLS C & E, & LOADING DOCKS
3' DIAMETER / 9'-6" CIRCUMFERENCE



=USABLE REG. AREA



=BLDG. SIGN HEADERS AT COLUMNS

*=OVERHEAD LIGHTING

GAS LINE COMES THROUGH A DROP FROM THE
CEILING AND IS DONE BY RIGGING



KEEP CLEAR AREA

< =FIRE STROBE (HEIGHT: 6' - 7' - ALL HALLS)

◄ =FIRE STROBE (E HALL COLUMNS ONLY 9'-9.625")

FX =FIRE EXTINGUISHER

FHC =FIRE DEPT. CABINET

◦ FHB =FIRE HOSE BIB (AT COLUMNS)

☒ =WATER AND DRAIN LOCATED IN HALL D ONLY 60' ON CEN

☐ =UTILITIES FLOOR BOX - ALL PORTS CONTAIN:
WATER AND DRAIN, COMP. AIR 90 PSI, PHONE 6 PAIR JAC
CONDUIT TO UTILITY TUNNEL
COMBINATION 20 AMP, 120 V & 20 AMP, 208 V 1 PHASE
POWER OUTLET 100 AMP 120/208 V 3 PHASE 4 W

○ =UTILITIES FLOOR BOX
PHONE 6 PAIR JACK
COMBINATION 20 AMP, 120 V & 20 AMP, 208 V 1 PHASE
POWER OUTLET 60 AMP 120/208 V 3 PHASE 4 W

▤ =LOBBY BENCHES

WFM =WAY-FINDER MONITOR

☑ =AUTOMATED EXTERNAL DEFIBRILLATORS

AED

ATM =ATM (LARGE)

ATM =ATM (SMALL)

⊖ =DIGITAL SIGNS AT COLUMNS



=DIGITAL SIGNS AT COLUMNS
BUILDING LEVEL NUMBER







